

KDS

KITCHEN DISPLAY SYSTEM

Robust & Total Integration
Fanless & Ventless
Aluminium Die-Cast Casing
Industrial Grade Components
IP66 - Water, Dust & Grease Proof
Removable Solid State Drive
Wireless LAN (Optional)
VESA Mount Capability



SAFE & EFFICIENT WORK ENVIRONMENT

SEVOR





Senor's Kitchen Display System (KDS) displays order information clearly and effectively in a fast paced kitchen environment.

As a fanless & ventless terminal, it is protected from water, dust, steam and grease. Its aluminum die-cast casing dissipates heat all round, offering protection from extreme temperature and humidity that is commonly present in the kitchen setting.

The KDS can also be used as an industrial grade panel PC terminal, offering solid-state device with no moving parts. Its robust & solid physics greatly extends the hardware life, as well as enhances reliability & performance in all harsh surroundings.

Specifications			
	KDS 65T/65G	KDS 66T/66G	KDS 670
Main Board	GST-378	GST-388	GST-388
CPU Supports	AMD LX -800 500Mhz, w/ 128K L2 Cache	Intel N270 1.6GHz, w/ 512KB Cache	
System Memory	1 x SODIMM DDR socket (Notebook type 200-Pin) Supports DDR333/400 DIMM up to 1G	Two SODIMM DDR2 socket / up to 2GB DDR2 533	
Display Function	Integrated FPU support Intel MMX and AMD 3D Now Technology Instruction sets, Video Memory up to 254MB shared with system	Intel 945GSE Chipset Dynamic Video Memory up to 224MB shared with system	
LCD Touch Panel			
LCD Size	15" TFT LCD	15" TFT LCD	17" TFT LCD
Resolution	1024 x 768		1280 x 1024 pixels
Brightness	250 cd/ m ²	250 cd/m ² / 350 cd/m ²	250 cd/ m ² , 380 cd/ m ² , 500 cd/ m ²
Touch Screen	Senor 5-wire Resistive Touch (KDS 65T) Glass only (KDS 65G)	5-wire Resistive Touch (KDS 66T) Glass only (KDS 66G)	5-wire Resistive Touch, SAW Touch, Capacitive Touch, Glass only (KDS 670g)
Connectivity			
IDE/SATA	44 pins box-header x1 for HDD (Master) Compact Flash type II socket x1 for CF card(Slave/ Removable)	SATA: 1 x socket for HDD / 1x Compact Flash socket	
LAN	1 x RJ-45 LAN port 10/100 Internal 802.11g Wireless LAN (Option)	1 x RJ-45 LAN port 10/100/1000 Mbps Internal 802.11g Wireless LAN (Option)	
USB	3x External USB ports		
Parallel	1 x Mini Printer Port		
PS/2kb	1 x Mini Din Jack		
Audio	1 X Earphone Jack For Line- out		
Mechanical & Environment			
Dimension	389 x 96 x 334mm		446 x 118 x 388mm
Weight	8.5 Kg	7 Kg	9 Kg
Smart Features	Aluminum Casing, Fanless & Ventless System		
Infrared Function	Built-in Infrared K/B & Mouse Receiver(Optional)		
Water And Dust Resistant	IP66		
Safety Certifications	FCC / CE / CCC / TUV / CB		
Storage Temperature	-20~60C		
Operating temperature	0~40 C		
Relative Humidity	20%-90% (non-condensing)		
Software			
Operation System	DOS/Windows XP/CE5.0/Linux/WEPOS	Windows 2000 / XP / POS Ready 2009	
Self-testing program	SENR self-testing software		
Peripheral Options			
Infrared Keyboard	Keyboard wedge interface		

[Note: The product information and specifications are subject to change without notice]



Retail Solutions Pty Ltd
 121 Payneham Road
 St. Peters SA 5069
 p: 08 8363 2988 f: 08 8363 2991
 e : sales@retail-solutions.com.au
 w : www.retail-solutions.com.au